

CRS-36

Creaser

Avoid cracking on digitally-printed, heavy-weight stock with accurate, easy-to-use impact creaser



Features

- 1. Quick and easy set-ups are performed at the color touch screen control console.
- 2. Select from a wide variety of scoring patterns.
- 3. Ideal for book jackets, restaurant menus, greeting cards and all digital print applications.
- 4. Crease even heavy stocks for high quality perfect binding with sharp corners.



Ideal for heavy stock and digital printing: eliminates fiber cracking when folding

Operation console

Graphical touch screen enables easy settings for different applications.









Impact creasing Samples

Impact creasing section

Impact creasing depth can be adjusted according to the paper thickness.

Clean and sharp creases can be made even on heavier and laminated stock.

Delivery tray

Creased sheets are delivered at a comfortable height for easy handling.

The tray can be folded down for space efficiency when the impact creaser is not in use.



CRS-30 Major Specifications		
Installation Type	Floor Model	
Sheet Feeding System	Manual Feed	
Sheet Size		Width x Length Max. 364 x 650 mm / 14.33" x 25.59" Min. 140 x 180 mm / 5.52" x 7.09"
	(englis	A3 / A4 / A5 / B4 / B5 8.5 x 11" / 8.5 x 14" / 11 x 17" / 12 x 18"
Sheet Weight Range	Normal Paper, Coated Paper 81.4 to 407 gsm / 24 lb bond to 150 lb cover	
Creasing Mechanism	One set of positive and negative	
Number of Creasing Lines	Max. Eight Creasing Lines	
Production Speed	Length 430 mm / 16.92", Four Creasing Lines, 4 seconds per sheet	
Voltage / Frequency	Single Phase 115 V, 230 V, 50 / 60 Hz	
Rated Current	Single Phase 115 to 120 V, 50 / 60 Hz, 1.1 A Single Phase 200 to 240 V, 50 / 60 Hz, 0.5 A	
Machine Dimensions	W1,326 x D630 x H1,272 mm / W52.3" x D24.9" x H50.1"	
	When the delivery tray is folded W752 x D630 x H1,272 mm / W29.7" x D24.9" x H50.1"	
Machine Weight	85 kg / 187.4 lb	

CRS-36 Major Specifications

Distributed by

^{*}The machine design and specifications are subject to change without any notice.